

**Din Rail Power Supply
30W**



Slimline Din rail mounting power supply. Wide input voltage range. Comprehensive over current and over voltage protection.

Input voltage	85-264VAC, 105-370VDC
Efficiency	80%
Power output	30W
Voltage adjustments	+/- 10% via Pot
Ripple voltage	1% pk to pk
Overcurrent protection	105%
Power factor	n/a
IP Rating	IP20 (finger safe)
Approvals	UL, UL 508, TUV, CE
Dimensions	H = 95mm, W = 36mm, D = 108mm

Stock No.	Manf Ref'	Output	Unit Price		
			1-4	5-9	10+
5502634	PS5R-SC12	12VDC/2.5A	52.80	51.22	49.63
5502633	PS5R-SC24	24VDC/1.3A	44.44	43.11	41.81

**Din Rail Power Supply
60W**



Slimline Din rail mounting power supply. Wide input voltage range. Comprehensive over current and over voltage protection.

Input voltage	85-264VAC, 105-370VDC
Efficiency	80%
Power output	60W
Voltage adjustments	+/- 10% via Pot
Ripple voltage	1% pk to pk
Overcurrent protection	105%
Power factor	Corrected to EN61000-3-2
IP Rating	IP20 (finger safe)
Approvals	UL, UL 508, TUV, CE
Dimensions	H = 95mm, W = 36mm, D = 108mm

Stock No.	Manf Ref'	Output	Unit Price		
			1-4	5-9	10+
5502632	PS5R-SD24	24VDC/2.5A	56.30	54.61	52.97

**Din Rail Power Supply
90W**



Slimline Din rail mounting power supply. Wide input voltage range. Comprehensive over current and over voltage protection.

Input voltage	85-264VAC, 105-370VDC
Efficiency	80%
Power output	90W
Voltage adjustments	+/- 10% via Pot
Ripple voltage	1% pk to pk
Overcurrent protection	105%
Power factor	Corrected to EN61000-3-2
IP Rating	IP20 (finger safe)
Approvals	UL, UL 508, TUV, CE
Dimensions	H = 115mm, W = 46mm, D = 121mm

Stock No.	Manf Ref'	Output	Unit Price		
			1-4	5-9	10+
5502510	PS5R-SE24	24VDC/3.75A	67.30	65.28	63.32

**Din Rail Power Supply
120W**



Slimline Din rail mounting power supply. Wide input voltage range. Comprehensive over current and over voltage protection.

Input voltage	85-264VAC, 105-350VDC
Efficiency	80%
Power output	120W
Voltage adjustments	+/- 10% via Pot
Ripple voltage	1% pk to pk
Overcurrent protection	105%
Power factor	Corrected to EN61000-3-2
IP Rating	IP20 (finger safe)
Approvals	UL, UL 508, TUV, CE
Dimensions	H = 115mm, W = 50mm, D = 129mm

Stock No.	Manf Ref'	Output	Unit Price		
			1-4	5-9	10+
5502511	PS5R-SF24	24VDC/5.0A	96	93.12	90.33

<<12

**Din Rail Power Supply
240W**



Slimline Din rail mounting power supply. Wide input voltage range. Comprehensive over current and over voltage protection.

Input voltage	85-264VAC, 105-350VDC
Efficiency	80%
Power output	240W
Voltage adjustments	+/- 10% via Pot
Ripple voltage	1% pk to pk
Overcurrent protection	105%
Power factor	Corrected to EN61000-3-2
IP Rating	IP20 (finger safe)
Approvals	UL, UL 508, TUV, CE
Dimensions	H = 125mm, W = 80mm, D = 143mm

Stock No.	Manf Ref'	Output	Unit Price		
			1-4	5-9	10+
5502512	PS5R-SG24	24VDC/10A	139.00	134.83	130.79