


**SNR Slimline  
6A SPCO**



A space saving package comprising relay, and IP20 DIN rail mounting base measuring only 6.2mm wide. Relays and sockets can also be purchased separately. Base fitted with LED indicator and back emf protection (diode dc version). Note 230V ac version uses 60V dc relay, socket has integral diode bridge,

Contact arrangement	Single pole changeover
Contact material	Silver tin oxide carry, with gold plate option
Continuous current	6A at 230 / 400 V ac
Contact load min	
Operate / release time	5ms / 2ms
Nominal coil power	170mW
Coil resistance.ohm	848 (12V), 3390 (24V)
Mechanical life	10 Million
Dielectric strength	4000Vrms
Temperature	-30°C to + 55°C
Approvals	VDE, UL, CSA
L = 80, W = 6.2, H = 94	

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4954078	ST3P3LB2	SPCO-12VDC	6.00	5.40	5.10
4954081	ST3P3LC4	SPCO-24VDC	6.00	5.40	5.10
4954096	ST3P2LC4	SPCO-24VDC GOLD	6.00	5.40	5.10
4954082	ST3P3TP0	SPCO-230VAC/DC	7.50	6.75	6.38