


**Ice Proof Pushbutton 10A
Plastic Housing IP67**



The ITW switches 76-91 flexibutton series is a robust momentary action pushbutton designed for demanding applications, featuring an ice proof flexible actuator which is also flame retardant to UL94-V0. These will fit a standard 22.5mm cut out or by reversing the locknut a 25mm hole. Optional gold contacts, 2 poles or sealed with flying leads.

Current rating	Min 10mA at 5Vdc silver, 10A at 230Vac and 28Vdc
Contact arrangement	1 N/O and 1N/C fine silver
IP Rating	IP67
Temperature	-40°C to +80°C
Connection	2.8mm faston/solder terminals
Housing/actuator	Plastic, Poletter block amide
Dimensions	Bezel 30.0mm, depth 20.7mm, cutout 22.5mm
Panel thickness	Up to 6mm

Stock No.	Manf Ref'	Type	Unit Price		
			1-9	10-24	25+
9351040	76-9111/439088	FLEXI BUTTON WHITE	5.13	4.87	4.62
9351041	76-9112/439088	FLEXI BUTTON RED	5.13	4.87	4.62
9351042	76-9113/439088	FLEXI BUTTON GREEN	5.13	4.87	4.62
9351043	76-9114/439088	FLEXI BUTTON BLUE	5.13	4.87	4.62
9351044	76-9115/439088	FLEXI BUTTON YELLOW	5.13	4.87	4.62
9351045	76-9116/439088	FLEXI BUTTON BLACK	5.13	4.87	4.62

**Pushbutton 10A
Diecast Housing IP67**



The ITW switches 76-94 is a range of ultra rugged pushbuttons with diecast zinc bodies and actuators. Available as a momentary pushbutton with flush, raised or a domed head and a rotary switch. Matching panel indicator lamps are also available.

Current rating	Min 10mA at 5Vdc silver, Max 10A at 230Vac and 28Vdc
Dielectric strength	1000Vac rms
Contact arrangement	1 N/O and 1N/C fine silver
IP Rating	IP67
Temperature	-40°C to +125°C
Connection	2.8mm faston/solder terminals
Housing/actuator	Diecast zinc, diecast zinc
Dimensions	Bezel 30.0mm, depth 28.0mm, cutout 22.5mm with flats
Panel thickness	Up to 6mm

Stock No.	Manf Ref'	Type	Unit Price		
			1-9	10-24	25+
9351003	76-9410/439088R	FLUSH RED MOMENTARY	10.85	10.31	9.77
9351000	76-9410/439088G	FLUSH GREEN MOMENTARY	9.71	9.22	8.74
9351005	76-9410/439088B	FLUSH BLACK MOMENTARY	9.60	9.12	8.64
9351007	76-9410/439088N	FLUSH BLUE MOMENTARY	9.60	9.12	8.64
9351009	76-9420/439088R	RAISED RED MOMENTARY	9.60	9.12	8.64
9351010	76-9420/439088G	RAISED GREEN MOMENTARY	9.60	9.12	8.64
9351012	76-9420/439088N	RAISED BLUE MOMENTARY	9.60	9.12	8.64
9351014	76-9450/439088R	DOMED RED MOMENTARY			
9351015	76-9450/439088G	DOMED GREEN MOMENTARY	11.47	10.90	10.32
9351016	76-9450/439088B	DOMED BLACK MOMENTARY	11.47	10.90	10.32
9351017	76-9470/439088R	ROTARY RED DOT	14.38	13.66	12.94
9351018	76-9470/439088G	ROTARY GREEN DOT	14.58	13.85	13.12