

3 & 4 Pole Enclosed Isolators, IP67



A range of high quality 3 and 4 pole switch disconnectors in polycarbonate enclosures protected to IP67. This range of switches feature a recessed switch handle to give the higher IP protection level. All switches are interlocked with lid to prevent removal in the 'ON' position and are padlockable in the 'OFF' position. An earth terminal is included in all enclosures.

Rated Current (A)	20	25	32	40	63
No. of poles	3-4	3-4	3-4	3-4	3-4
Rated insulation voltage (V)	690	690	690	690	690
Motor rating, AC23A (kW)	5.5	7.5	11	15	22
IP Rating	IP67	IP67	IP67	IP67	IP67
Max. cable size (sq. mm)	2.5	6	6	16	16
Height (mm)	121	121	121	190	190
Width (mm)	86	86	86	100	100
Depth (mm)	90	90	90	93	93
Conforms to	IEC 60 947, IEC 60 204, BS EN 60 947, BS EN 60 204				

Stock No.	Manf Ref ¹	Current	No. Poles	Unit Price		
				1-4	5-9	10-24
8901133	KG10T203/GBA270KS1V	20A	3	15.83	15.04	14.25
8901211	KG20T203/GBA270KS1V	25A	3	17.76	16.87	15.98
8901265	KG32T203/GBA270KS1V	32A	3	20.49	19.47	18.44
8901292	KG41T203/GBA270KL1V	40A	3	31.39	29.82	28.25
8901319	KG64T203/GBA270KL1V	63A	3	35.64	33.86	32.08
8901346	KG80T203/GBA901KL	80A	3	59.17	56.21	53.25
8901139	KG100T203/GBA901KL	100A	3	67.22	63.86	60.50
8901136	KG10T204/GBA290KS1V	20A	4	17.08	16.23	15.37
8901214	KG20T204/GBA290KS1V	25A	4	21.95	20.85	19.76
8901268	KG32T204/GBA290KS1V	32A	4	25.38	24.11	22.84
8901295	KG41T204/GBA290KL1V	40A	4	40.71	38.67	36.64
8901322	KG64T204/GBA290KL1V	63A	4	40.71	38.67	36.64
8901349	KG80T204/GBA920KL	80A	4	65.91	62.61	59.32
8901142	KG100T204/GBA920KL	100A	4	76.54	72.71	68.89

16 >

6 Pole Enclosed Isolators IP67 & IP65



A range of high quality 6 pole switch disconnectors in polycarbonate enclosures. This range of switches up to and including 63Amp feature recessed switch handles which protect the enclosures to IP67. The 80 & 100Amp models feature prominent switch handles which protect the enclosures to IP65. All switches are interlocked with the lid to prevent removal in the 'ON' position and are padlockable in the 'OFF' position. The 6 pole models, 32 Amp to 100 Amp, have 2 normally open auxiliary contacts (early break) incorporated. An earth terminal is included in all enclosures.

Rated Current (A)	20	25	32	40	63	80	100	80	100
No. of poles	6	6	6	6	6	6	6	3-4	3-4
Auxiliary contacts (2N/O)	NO	NO	YES	YES	YES	YES	YES	NO	NO
Rated insulation voltage (V)	690	690	690	690	690	690	690	690	690
Motor rating, AC23A (kW)	5.5	7.5	11	15	22	30	30	37	37
IP Rating	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Max. cable size (sq. mm)	2.5	6	6	16	16	35	35	35	35
Height (mm)	121	190	190	250	250	280	280	250	250
Width (mm)	86	100	100	145	145	190	190	145	145
Depth (mm)	90	90	90	100	100	180	180	100	100
Conforms to	IEC 60 947, IEC 60 204, BS EN 60 947, BS EN 60 204								

Stock No.	Manf Ref ¹	Current	No. Poles	Protection	Unit Price		
					1-4	5-9	10-24
8901166	KG10BT206/GBA946-KS	20A	6	IP67	23.59	22.41	21.23
8901217	KG20BT206/GBA946-KL	25A	6	IP67	40.10	38.10	36.09
8901271	KG32BT206/GBA906-KL	32A	6 + AUX	IP67	50.97	48.42	45.87
8901301	KG41BT206/GBA906-KL	40A	6 + AUX	IP67	63.40	61.50	59.60
8901328	KG64BT206/GBA906-KL	63A	6 + AUX	IP67	70.21	66.70	63.19
8901355	KG80T206/GBA907ST	80A	6 + AUX	IP65	160.11	152.10	144.10
8901148	KG100T206/GBA907ST	100A	6 + AUX	IP65	176.15	167.34	158.54