

**24 Vdc Din Rail PSU
18W Plastic Case**



A modern single phase din rail mounting power supply providing a 24Vdc output. Wide input voltage range. Comprehensive over current and over voltage protection. Outputs may be wired in parallel using external diodes.

Input Voltage	90-265VAC, 120-370VDC
Line frequency	47 - 63HZ
Efficiency	77%
Power Output	18W
Voltage Adjustments	22.5 to 28.5Vdc
Ripple Voltage	50mV
Overcurrent Protection	yes
IP Rating	IP20 (Finger Safe)
Approvals	UL, cUL ,TUV, CE
Dimensions	D = 115mm, W = 23mm, H = 90mm

Stock No.	Manf Ref'	Output	Unit Price 1-4
2669477	BAE0001	24VDC/0.75A	38.00

**24 Vdc Din Rail PSU
30W Plastic Case**



A modern single phase din rail mounting power supply providing a 24Vdc output. Wide input voltage range. Comprehensive over current and over voltage protection. Outputs may be wired in parallel using external diodes. Output ready indication via relay contact.

Input Voltage	85-264VAC, 90-375VDC
Line frequency	47 - 63HZ
Efficiency	86%
Power Output	30W
Voltage Adjustments	22.5 to 28.5Vdc
Ripple Voltage	50mV
Overcurrent Protection	yes
IP Rating	IP20 (Finger Safe)
Approvals	UL, cUL ,TUV, CE
Dimensions	D = 115mm, W = 40mm, H = 90mm

Stock No.	Manf Ref'	Output	Unit Price 1-4
2669480	BAE0004	24VDC/1.25A	45.00

**24 Vdc Din Rail PSU
60W Plastic Case**



A modern single phase din rail mounting power supply providing a 24Vdc output. Wide input voltage range. Comprehensive over current and over voltage protection. Output may be wired in parallel using external diodes. Output ready indication via relay contact. DC low red led.

Input Voltage	85-264VAC, 90-375VDC
Line frequency	47 - 63HZ
Efficiency	89%
Power Output	60W
Voltage Adjustments	22.5 to 28.5Vdc
Ripple Voltage	50mV
Overcurrent Protection	yes
IP Rating	IP20 (Finger Safe)
Approvals	UL, cUL ,TUV, CE
Dimensions	D = 115mm, W = 40mm, H = 90mm

Stock No.	Manf Ref'	Output	Unit Price 1-4
2669483	BAE0005	24VDC/2.5A	59.00

**24 Vdc Din Rail PSU
120W Metal Case**



A modern single phase din rail mounting power supply providing a 24Vdc output. Wide input voltage range. Comprehensive over current and over voltage protection. A selector switch allows outputs to wired in parallel without external components. Output ready indication via relay contact. Dc low red led.

Input Voltage	90-264VAC, 210-370VDC
Line frequency	47 - 63HZ
Efficiency	86%
Power Output	120W
Voltage Adjustments	22.5 to 28.5Vdc
Ripple Voltage	50mV
Overcurrent Protection	yes
IP Rating	IP20 (Finger Safe)
Approvals	UL, cUL ,TUV, CE
Dimensions	D = 115mm, W = 63mm, H = 123mm

Stock No.	Manf Ref'	Output	Unit Price 1-4
2669486	BAE0006	24VDC/5.0A	79.00

<<12