

**24 Vdc Din Rail PSU
240W Metal Case**



A modern single phase din rail mounting power supply providing a 24Vdc output. Wide input voltage range. Comprehensive over current and over voltage protection. A selector switch allows outputs to wired in parallel without external components. Output ready indication via relay contact. Dc low red led.

Input Voltage	90-264VAC, 210-370VDC
Line frequency	47 - 63HZ
Efficiency	89%
Power Output	240W
Voltage Adjustments	22.5 to 28.5Vdc
Ripple Voltage	100mV
Overcurrent Protection	yes
IP Rating	IP20 (Finger Safe)
Approvals	UL, cUL ,TUV, CE
Dimensions	D = 115mm, W = 83mm, H = 123mm

Stock No.	Manf Ref'	Output	Unit Price 1-4
2669489	BAE0002	24VDC/10A	129.00

**24 Vdc Din Rail PSU
480W Metal Case**



A modern single phase din rail mounting power supply providing a 24Vdc output. Wide input voltage range. Comprehensive over current and over voltage protection. A selector switch allows outputs to wired in parallel without external components. Output ready indication via relay contact. Dc low red led.

Input Voltage	90-265VAC, 120-370VDC
Line frequency	47 - 63HZ
Efficiency	89%
Power Output	480W
Voltage Adjustments	22.5 to 28.5Vdc
Ripple Voltage	100mV
Overcurrent Protection	yes
IP Rating	IP20 (Finger Safe)
Approvals	UL, cUL ,TUV, CE
Dimensions	D = 115mm, W = 175mm, H = 123mm

Stock No.	Manf Ref'	Output	Unit Price 1-4
2669492	BAE0003	24VDC/20A	198.00

**24 Vdc Din Rail 3 Phase PSU
120W Metal Case**



A modern three phase din rail mounting power supply providing a 24Vdc output. Wide input voltage range. Comprehensive over current and over voltage protection. Outputs may be wired in parallel using external diodes. Output ready indication via relay contact. Dc low red led.

Input Voltage	340-575VAC, 480-820VDC
Line frequency	47 - 63HZ
Efficiency	89%
Power Output	120VA
Voltage Adjustments	22.5 to 28.5Vdc
Ripple Voltage	100mV
Overcurrent Protection	yes
IP Rating	IP20 (Finger Safe)
Approvals	UL, cUL ,TUV, CE
Dimensions	D = 112mm, W = 74mm, H = 123mm

Stock No.	Manf Ref'	Output	Unit Price 1-4
2669495	BAE0007	24VDC/5A	109.00

**24 Vdc Din Rail 3 Phase PSU
240W Metal Case**



A modern three phase din rail mounting power supply providing a 24Vdc output. Wide input voltage range. Comprehensive over current and over voltage protection. A selector switch allows outputs to wired in parallel without external components. Output ready indication via relay contact. Dc low red led.

Input Voltage	340-575VAC, 480-820VDC
Line frequency	47 - 63HZ
Efficiency	90%
Power Output	240VA
Voltage Adjustments	22.5 to 28.5Vdc
Ripple Voltage	100mV
Overcurrent Protection	yes
IP Rating	IP20 (Finger Safe)
Approvals	UL, cUL ,TUV, CE
Dimensions	D = 112mm, W = 89mm, H = 123mm

Stock No.	Manf Ref'	Output	Unit Price 1-4
2669498	BAE0008	24VDC/10A	159.00