


Voltmeter Selector Switch 3 Phase



3 phase, 3 wire voltmeter selector switch with 'OFF'. Single hole Ø22mm mounting.



Rated thermal current 20 Amp
 Nominal voltage 690 V
 Motor rating AC-23A 7.5 kW
 Dielectric strength 6 kV
 Conforms to IEC 947-3, EN60947-3, VDE 0660 part 107

Dimensions (mm)	L	A	B	C	M
	52.5	49	43	6 max	20

Note:
 R (red phase) Live 1
 Y (yellow phase) Live 2
 B (blue phase) Live 3
 N Neutral

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10-24
8901001	CA10A004622FT2	VOLTAGE SW.	11.03	10.70	10.37

Voltmeter Selector Switch 3 Ph/Ph, 3 Ph/Neutral



3 phase/phase and 3 phase/neutral voltmeter selector switch with centre 'OFF'. Single hole Ø22mm mounting. Two different types of escutcheon plate, 1 standard escutcheon 49 x 49mm and 1 extended escutcheon 49 x 60.4mm with 'Voltmeter' legend at the top.



Rated thermal current 20 Amp
 Nominal voltage 690 V
 Motor rating AC-23A 7.5 kW
 Dielectric strength 6 kV
 Conforms to IEC 947-3, EN60947-3, VDE 0660 part 107

Dimensions (mm)	L	A	B	C	M
	52.5	49	43	6 max	20

Note:
 R (red phase) Live 1
 Y (yellow phase) Live 2
 B (blue phase) Live 3
 N Neutral

Stock No.	Manf Ref'	Escutcheon	Unit Price		
			1-4	5-9	10-24
8901004	CA10A007622FT2	49 x 49	13.90	13.48	13.07
8901007	CA10A007623FT2	49 x 60.4	14.44	14.01	13.57

Ammeter Selector Switch



Single pole ammeter selector switches with centre 'OFF' to use with 3 current transformers. Single hole Ø22mm mounting. Two different types of escutcheon plate, 1 standard escutcheon 49 x 49mm and 1 extended escutcheon 49 x 60.4mm with 'Ammeter' legend at the top.

Rated thermal current 20 Amp
 Nominal voltage 690 V
 Motor rating AC-23A 7.5 kW
 Dielectric strength 6 kV
 Conforms to IEC 947-3, EN60947-3, VDE 0660 part 107

Dimensions (mm)	L	A	B	C	M
	52.5	49	43	6 max	20

Note:
 R (red phase) Live 1
 Y (yellow phase) Live 2
 B (blue phase) Live 3
 N Neutral

Stock No.	Manf Ref'	Escutcheon	Unit Price		
			1-4	5-9	10-24
8901010	CA10A048621FT2	49 x 49	13.90	13.48	13.07
8901013	CA10A048622FT2	49 x 60.4	14.44	14.01	13.57

22mm Blanking Plug



22mm blanking plug suitable for blanking off unused or unwanted holes in panels of up to 6mm thickness. Comprising of threaded blanking plug, rubber washer and locknut.

IP Rating IP65
 Material Plastic

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10-24
8901637	PN207/58	BLANKING PLUG	1.58	1.53	1.49