

M18 Capacitive



A range of M18 capacitive proximity sensors available in flush mounting with 8mm sensing range or non flush with 12mm sensing range. This range feature complementary outputs NO and NC with 4 wire cable or connector.

Sensing range	Flush 8mm, non flush 12mm
Supply voltage	10-40 volt DC
Rated output current	200 mA
IP Rating	IP67
Housing material	Plastic or PTFE
Dimensions	18mm diameter, 83.5mm flush

Stock No.	Manf Ref'	Type	Connection	Unit Price	
				1-4	
3801626	CM18-08BPP-KC1	PNP NO/NC FLUSH	M12 4 PIN		50.39
3801530	CM18-08BPP-KW1	PNP NO/NC FLUSH	CABLE		49.64
3801545	CM18-08BNP-KC1	NPN NO/NC FLUSH	M12 4 PIN		50.39
3801629	CM18-12NPP-KC1	PNP NO/NC NON FLU	M12 4 PIN		48.93
3801632	CM18-12NPP-KC1	NPN NO/NC NON FLU	M12 4 PIN		48.93
3801635	CM18-08BPP-TW0	PNP NO/NC FLU PTFE	CABLE		80.94

M30 Capacitive



A range of M30 capacitive proximity sensors available in flush mounting with 16mm sensing range or non flush with 25mm sensing range. This range feature complementary outputs NO and NC with 4 wire cable or connector.

Sensing range	Flush 16mm, non flush 25mm
Supply voltage	20-250 VAC
Rated output current	500 mA
IP Rating	IP67
Housing material	Plastic
Dimensions	30mm diameter, 79mm flush

Stock No.	Manf Ref'	Type	Connection	Unit Price	
				1-4	
3801638	CM30-25NAP-KW1	TRIAC NO NON FLUSH	CABLE		64.81
3801641	CM30-16BAP-KW1	TRIAC N/O FLUSH	CABLE		64.81

Square Capacitive



Block style capacitive proximity sensor with a range of 25mm.

Sensing range	25mm
Supply voltage	10-40 volt DC
Rated output current	200 mA
IP Rating	IP67
Housing material	Plastic
Dimensions	15mm, 69.5mm, 35mm

Stock No.	Manf Ref'	Type	Connection	Unit Price	
				1-4	
3801644	CQ35-25NPP-KC1	PNP NO/NC	M12 4 PIN		56.69