



**RX1 Series
16A, SPCO**



Terminal Arrangements (bottom view)




Board Layout

A low profile single pole changeover PCB power relay with a clear case capable of switching 16A. Flux tight construction.


Contact arrangement Single pole changeover
 Contact material Silver nickel
 Continuous current 16A at 230 / 400V ac
 Contact load min.
 Operate / release time 7ms / 2ms
 Nominal coil power 520mW dc, 0.75 VA ac
 Coil resistance.ohm 50 (5V), 274 (12V), 1095 (24V), 32500 (230V ac)
 Mechanical life 5 Million
 Dielectric strength 4000V rms
 Temperature -40°C to + 85°C
 Approvals VDE, UL, CSA
 L = 29, W = 12.7, H = 15.7

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4954666	RX314012C	SPCO-12VDC	1.35	1.22	1.15
4954668	RX314024C	SPCO-24VDC	1.35	1.22	1.15
4954670	RX314730C	SPCO-230VAC	2.50	2.25	2.13

**RX1 Series
8A, DPCO**



Terminal Arrangements (bottom view)




Board Layout

A low profile double pole changeover PCB power relay with a clear case capable of switching 8A. Flux tight construction.


Contact arrangement Double pole changeover
 Contact material Silver nickel
 Continuous current 8A at 230 / 400V ac
 Contact load min.
 Operate / release time 7ms / 2ms
 Nominal coil power 520mW dc, 0.75 VA ac
 Coil resistance.ohm 50 (5V), 274 (12V), 1095 (24V), 32500 (230V ac)
 Mechanical life 5 Million
 Dielectric strength 4000V rms
 Temperature -40°C to + 85°C
 Approvals VDE, UL, CSA
 L = 29, W = 12.7, H = 15.7

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4954660	RX424012C	DPCO-12VDC	1.60	1.44	1.36
4954662	RX424024C	DPCO-24VDC	1.60	1.44	1.36
4954664	RX424730C	DPCO-230VAC	2.70	2.43	2.30

**PT Series, PCB Mount
6A, 4PCO**



Terminal Arrangements (bottom view)




Board Layout

A PCB mount version of the popular 14 pin 4 pole PT plug in relay with mechanical override lever. Specials without lever and LED indication available as are gold flashed contacts.


Contact arrangement Four pole changeover
 Contact material Silver nickel
 Continuous current 6A at 230V ac
 Contact load min. 12V dc 10mA standard contact
 Operate / release time 15ms / 10ms
 Nominal coil power 0.75 W dc, 1.0 VA ac
 Coil resistance.ohm 777 (24Vdc), 192 (24Vac), 19465 (230Vac)
 Mechanical life 30 Million dc, 20 Million ac
 Dielectric strength 2500V rms (coil to contact)
 Temperature -40°C to + 70°C
 Approvals UL, VDE

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4954608	PT571024	4PCO-24VDC	3.91	3.52	3.32
4954610	PT571730	4PCO-230VAC	3.91	3.52	3.32

**RT1 Series
12A, SPCO**



Terminal Arrangements (bottom view)



Board Layout

A low profile single pole PCB power relay capable of switching 12A. Fully sealed washtight construction.

Contact arrangement Single pole changeover
 Contact material Silver nickel
 Continuous current 12A at 230 / 400V ac
 Contact load min.
 Operate / release time 7ms / 3ms
 Nominal coil power 400mW
 Coil resistance.ohm 62 (5V), 360 (12V), 1449 (24V)
 Mechanical life 30 Million
 Dielectric strength 5000V rms
 Temperature -30°C to + 85°C
 Approvals VDE, UL, CSA
 L = 29, W = 12.7, H = 15.7

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4953035	RTB14005	SPCO-5VDC	1.75	1.58	1.49
4953036	RTB14012	SPCO-12VDC	1.75	1.58	1.49
4952748	RTB14024	SPCO-24VDC	1.75	1.58	1.49
4952750	RTB14730	SPCO-230VAC	2.70	2.43	2.30