


**ATEX Limit Switch
EEx 13 Plastic**




An explosion proof plastic bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts.

Actuator Plain plunger
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +65°C
 Termination Cable 1M
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification EX II 2D IP65 T80
 Approvals PTB 03 ATEX 1068X, IECEx

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441021	EEX13 10/1S	PLAIN PLUNGER	50.52	49.00	47.49

**ATEX Limit Switch
EEx 13 Plastic**




An explosion proof plastic bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts.

Actuator Ball plunger
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +65°C
 Termination Cable 1M
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification EX II 2D IP65 T80
 Approvals PTB 03 ATEX 1068X, IECEx

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441023	EEX13KU10/1S	BALL PLUNGER	52.52	50.94	49.37

**ATEX Limit Switch
EEx 13 Plastic**




An explosion proof plastic bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts.

Actuator Roller plunger
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +65°C
 Termination Cable 1M
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification EX II 2D IP65 T80
 Approvals PTB 03 ATEX 1068X, IECEx

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441025	EEX13R10/1S	ROLLER PLUNGER	52.36	50.79	49.22

**ATEX Limit Switch
EEx 13 Plastic**



An explosion proof plastic bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts.

Actuator Roller lever
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +65°C
 Termination Cable 1M
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification EX II 2D IP65 T80
 Approvals PTB 03 ATEX 1068X, IECEx

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441027	EEX13D10/1S	ROLLER LEVER	64.02	62.10	60.18