


Binary Code Decimal Switches 0 - 7



	0	1	2	3	4	5	6	7
1		X	X	X	X			
2			X	X		X	X	
3				X			X	X
4					X			X
5						X		
6							X	X
7								X



8 position binary coded decimal switch suitable for electronic applications. They will reliably switch 5mA at 30mVDC on account of a gold plated 'H' bridge contact system. Switch comprises of switch body, escutcheon plate and handle. Single hole Ø22mm mounting suitable for up to 6mm panel thickness.

Rated thermal current 6 Amp
 Nominal voltage 600 V
 Minimum voltage 3 mV
 Rated operational current 5 mA (AC21A)


Dimensions (mm) L A B C M
 Escutcheon 43 48 43 6 max 20

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10-24
8901568	CAD11A540-600-FT2	0-7 BCD	14.48	14.05	13.61

Binary Code Decimal Switches 0 - 9



	0	1	2	3	4	5	6	7	8	9
1		X	X	X	X	X	X	X	X	
2			X	X		X	X			
3				X			X			
4					X			X		
5						X				
6							X			
7								X		
8									X	
9										X



10 position binary coded decimal switch suitable for electronic applications. They will reliably switch 5mA at 30mVDC on account of a gold plated 'H' bridge contact system. Switch comprises of switch body, escutcheon plate and handle. Single hole Ø22mm mounting suitable for up to 6mm panel thickness.

Rated thermal current 6 Amp
 Nominal voltage 600 V
 Minimum voltage 3 mV
 Rated operational current 5 mA (AC21A)

Dimensions (mm) L A B C M
 Escutcheon 43 48 43 6 max 20

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10-24
8901571	CAD11A550-600-FT2	0-9 BCD	17.27	16.75	16.23

OFF-ON Load Break Switch Insulated Enclosure



Off-On rotary cam switches housed in high impact polycarbonate enclosures with escutcheon plate and handle. Earth terminal provided.

Rated thermal current 20 Amp
 Nominal voltage 600 V
 Rated operational current 20 A (AC21A), 5 A (AC15)
 Dielectric strength 6 kV
 IP Rating IP65
 Conduit entries 4 x 20mm ISO
 Conforms to IEC 947-3, EN60947-3, VDE 0660 part 107

Dimensions (mm) H W D
 1 pole 72 64 42
 3 pole 72 64 51

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10-24
8901574	KN1	1 POLE	12.29	11.68	11.06
8901577	KN3	3 POLE	15.74	14.95	14.17

Changeover with/without OFF, Load Break Switch Insulated Enclosure



Changeover rotary cam switches with 'OFF' in a 1 pole model or without 'OFF' in a 2 pole model, housed in high impact polycarbonate enclosures with escutcheon plate and handle. Earth terminal provided. Ideal for generator change-over and similar applications.

Rated thermal current 20 Amp
 Nominal voltage 600 V
 Rated operational current 20 A (AC21A), 5 A (AC15)
 Dielectric strength 6 kV
 IP Rating IP65
 Conduit entries 4 x 20mm ISO
 Conforms to IEC 947-3, EN60947-3, VDE 0660 part 107

Dimensions (mm) H W D
 1 pole 72 64 42
 3 pole 72 64 51

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10-24
8901580	KN2	1 POLE	13.63	12.95	12.27
8901583	KN10	2 POLE	16.93	16.08	15.24