
**Limit Switches** SAIA-BURGESS

## **Industrial Metal Housed Microswitch**





A single pole changeover microswitch housed in aluminium offering high reliability and long life in harsh industrial environments. Insert switch attached to lid provides quick and efficient installation. Available with a standard plunger actuator.

Electrical rating 15 A at 480 VAC, 15 A at 15 VDC (resistive) Single pole changeover / Fine silver M20, screw terminals & cup washers Contacts / Material Conduit entry

Mechanical life -10° C to +85° C

Temperature IP Rating **IP40** 


Housing / Plunger Aluminium alloy / Stainless steel

Operating force.N 4.2 Release force.N 1.7 Pre-travel.mm 0.5 Differential travel.mm 0.08 Overtravel.mm 46 UL, CSA Approvals

				Unit Price		
Stock No.	Manf Ref'	Туре	1-9	10-49	50-99	
2192101	MN6CTQMS	STND. PLUNGER	51.43	46.29	39.34	

## **Industrial Metal Housed Microswitch**





A single pole changeover microswitch housed in aluminium offering high reliability and long life in harsh industrial environments. Insert switch attached to lid provides quick and efficient installation. Available with an in-line roller plunger actuator.

Electrical rating 15 A at 480 VAC, 15 A at 15 VDC (resistive) Contacts / Material Single pole changeover / Fine silver Conduit entry M20, screw terminals & cup washers Mechanical life 105

-10° C to +85° C Temperature IP Rating IP40

Housing / Plunger


Aluminium alloy / Stainless steel Operating force.N 4.2

1.7 Release force.N Pre-travel.mm 8.0 Differential travel.mm 0.08 Overtravel.mm 3.56 UL, CSA Approvals

			Unit Price		
Stock No.	Manf Ref'	Туре	1-9	10-49	50-99
2192107	MN6CTQRMS	ROLLER PLUNGER	60.00	54.00	45.90

## **Industrial Metal Housed Microswitch**





A single pole changeover microswitch housed in aluminium offering high reliability and long life in harsh industrial environments. Insert switch attached to lid provides quick and efficient installation. Available with a cowled standard plunger actuator offering IP67 protection

Electrical rating 15 A at 480 VAC, 15 A at 15 VDC (resistive) Contacts / Material Single pole changeover / Fine silver Conduit entry M20, screw terminals & cup washers Mechanical life 10<sup>5</sup>

-10° C to +85° C Temperature


IP Rating IP67 (seal conduit entry with compound) Housing / Plunger Aluminium alloy / Stainless steel

Operating force.N 6.7 Release force.N 1.7 Pre-travel.mm 2 Differential travel.mm 0.08 Overtravel.mm 4.6 UL CSA Approvals

			Unit Price		
Stock No.	Manf Ref'	Туре	1-9	10-49	50-99
2192074	M9CTQMS	COWLED PLUNGER	50.00	45.00	38.25

## **Industrial Metal Housed Microswitch**





A single pole changeover microswitch housed in aluminium offering high reliability and long life in harsh industrial environments. Insert switch attached to lid provides quick and efficient installation. Available with a cowl protected roller lever adjustable through 360° horizontally and 235° vertically

15 A at 480 VAC, 15 A at 15 VDC (resistive) Electrical rating Single pole changeover / Fine silver Contacts / Material Conduit entry M20, screw terminals & cup washers Mechanical life 105

-10° C to +85° C Temperature

IP Rating IP67 (seal conduit entry with compound) Housing / Plunger Aluminium alloy / Stainless steel

Operating force.N 5 6 1.7 Release force.N Pre-travel.mm 10° 0.5° Differential travel.mm Overtravel.mm 6.5° UL. CSA Approvals

Type **2192077** M9CTQMSA ADJ. ROLLER LEVER 74.29 66.86 56.83