

**End Sensor  
M10**



A magnetically actuated reed switch housed in a threaded M10 Brass housing. Switching distance up to 41 mm dependent on magnet choice. N/O versions available.

Housing	Brass nickel plated
Contact arrangement	1 C/O rhodium
Max Voltage	250 VDC, 175 VAC
Max Current	C/O 0.25A
Switching Power	C/O 3VA/W
IP Rating	IP67
Temperature	-10°C to +85°C
Termination	Cable 1M
Operating distance	M100 14mm, M200 19mm, M300 25mm
Release distance	M100 18mm, M200 24mm, M300 29mm
Approvals	

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441100	RC201W	BRASS C/O RHOD	23.20	22.50	21.81

**End Sensing Magnetic  
M12**



A magnetically actuated reed switch housed in a threaded M12 Brass housing. Switching distance up to 41 mm dependent on magnet choice. N/O versions available with higher current rating.

Housing	Aluminium brass nickel plated
Contact arrangement	1 C/O rhodium
Max Voltage	250 VAC/DC
Max Current	C/O 0.5A
Switching Power	C/O RHOD 15VA/W
IP Rating	IP67
Temperature	-10°C to +85°C
Termination	Cable 1M
Operating distance	M100 2mm, M200 8mm, M300 29mm
Release distance	M100 10mm, M200 18mm, M300 42mm
Approvals	

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441102	RC23W	BRASS C/O RHOD	23.36	22.66	21.96

**End Sensor  
M18 Plastic**



A magnetically actuated reed switch housed in a threaded M18 plastic. Switching distance up to 36 mm dependent on magnet choice. N/O versions available with higher current rating.

Housing	Plastic
Contact arrangement	1 C/O rhodium
Max Voltage	250 VAC/DC
Max Current	C/O 0.5A
Switching Power	C/O RHOD 15VA/W
IP Rating	IP67
Temperature	-10°C to +80°C
Termination	Cable 1M
Operating distance	M100 10mm, M200 16mm, M300 33mm
Release distance	M100 15mm, M200 18mm, M300 37mm
Approvals	

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441104	RC301W	PLASTIC C/O RHOD	22.13	21.47	20.80

**End Sensor  
RC 60**



A magnetically actuated reed switch housed in a partially threaded plastic body. Switching distance up to 33 mm dependent on magnet choice. N/O versions available with higher current rating.

Housing	Plastic
Contact arrangement	1 C/O rhodium
Max Voltage	250 VAC/DC
Max Current	C/O 0.5A
Switching Power	C/O RHOD 15VA/W
IP Rating	IP67
Temperature	-10°C to +80°C
Termination	Cable 1M
Operating distance	M100 4mm, M200 9mm, M300 30mm
Release distance	M100 13mm, M200 19mm, M300 44mm
Approvals	

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441106	RC601W	PLASTIC C/O RHOD	18.12	17.58	17.03