

<<40

Atex Signal Tower 740 Series



An Explosion proof signal tower certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Protection achieved by flame proof enclosure. LED model gives up to 100000 hours life. Also available with 2 tiers or illumination via 24Vdc or 230Vac filament bulb.

Housing	Aluminium/glass
Current consumption	45mA per tier (LED)
IP Rating	IP66
Temperature	minus 20 to +40 Deg C
Termination	3/4"NPT cable gland
Ex Certification	EX II 2G EEx d II C T6
Ex Certification	Ex II 2D IP66 85deg
Approvals	LCIE 97 EX6012
Dimensions 3 tier overall	Height 425mm, Diam 155mm

Stock No.	Manf Ref'	Type	Unit Price 1-4
2201006	740-210-55	LED 24VDC RED/YELLOW/GREEN	540.33

Ex LED Signal Tower 741 Series



An Explosion proof signal tower certified for Ex zones 1 and 2 achieved by combination of encapsulation "m" and intrinsic safety "ib" with connection area "e". External zener barrier not required. LEDs give up to 100000 hours life. Also available with only 2 tiers.

Housing	Polyester, PC
Current consumption	< 90mA
IP Rating	IP65
Temperature	minus 20 to +50 Deg C
Termination	Cable gland and terminal chamber
Ex Certification	EX II 2G EEx me ib II C T6
Approvals	PTB 06 ATEX 2005
Dimensions 3 tier overall	H 228mm, W 77mm, L 75mm

Stock No.	Manf Ref'	Type	Unit Price 1-4
2201009	741-130-55	LED 24VDC RED/YELLOW/GREEN	368.61

Ex Installation Beacon M20 Thread



An Ex LED permanent beacon with an M20 thread. Rated for zones 2 and 22. Other colours available.

Housing	PC, transparent
Current consumption	<45 mA
IP Rating	IP65
Temperature	minus 20 to +50 Deg C
Termination	Cable gland and terminal chamber
Ex Certification	EX II 3G Ex nA II T4 see note
Approvals	BVS 05 E041 U
Dimensions	H 30.5mm, Diam 28.7mm

Stock No.	Manf Ref'	Type	Unit Price 1-4
2201010	770-100-55	LED 24VDC RED	69.77

Ex Installation Beacon M22 Thread



An Ex LED permanent beacon with an M22 thread suitable for control cabinets. Rated for zones 2 and 22. Other colours available.

Housing	PC, transparent
Current consumption	<45 mA
IP Rating	IP65
Temperature	minus 20 to +50 Deg C
Termination	Cable gland and terminal chamber
Ex Certification	EX II 3G Ex nA II T4 see note
Approvals	BVS 05 E041 U
Dimensions	H 30.5mm, Diam 28.7mm

Stock No.	Manf Ref'	Type	Unit Price 1-4
2201012	771-100-55	LED 24VDC RED	71.01