

ATEX Rope Switch



An explosion proof rope/pullwire switch certified for use in Ex zone 1 and 2 as well as dust groups 21 and 22. Lever release and position indication. Ask for 3D version for group 22 certification.

Housing	Aluminium, plastic cover
Contact arrangement	1 N/O and 1 N/C
Electrical rating	6A at 250 Vac
IP Rating	IP67
Temperature	-20°C to +65°C
Termination	Cable 1M
Ex Certification	EX II 2G EEx d II C T6
Ex Certification	Ex II 2D IP65 T80
Approvals	PTB06 ATEX 1050X

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441090	EEXZS8010/1SWVD	1N/C+1N/O	183.70	178.19	172.68

ATEX Foot Switch



An explosion proof foot switch certified for use in Ex zone 1 and 2 as well as dust groups 21 and 22. Snap action contacts also available. Ask for 3D version for group 22 certification.

Housing	Aluminium
Contact arrangement	1 N/O and 1 N/C positive break
Electrical rating	6A at 250 Vac
IP Rating	IP65
Temperature	-20°C to +65°C
Termination	Cable 3M
Ex Certification	EX II 2G EEx d II C T6
Ex Certification	Ex II 2D IP65 T80
Approvals	PTB03 ATEX 1070X

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441092	EEXGF110/1S		133.03	129.04	125.05

ATEX Foot Switch



An explosion proof foot switch with protective shield certified for use in Ex zone 1 and 2 as well as dust groups 21 and 22. Snap action contacts also available. For category Ex dust zone 22 ask for suffix 3D version.

Housing	Aluminium
Contact arrangement	1 N/O and 1 N/C positive break
Electrical rating	6A at 250 Vac
IP Rating	IP65
Temperature	-20°C to +65°C
Termination	Cable 3M
Ex Certification	EX II 2G EEx d II C T6
Ex Certification	Ex II 2D IP65 T80
Approvals	PTB03 ATEX 1070X

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441094	EEXGFS110/1S		139.65	135.46	131.27