## 782XDXH10-120A

Harmony, Hermetically sealed plug-in relays, 3 A, 4 CO, 120 V AC





## Main

| Range of product              | Harmony Electromechanical Relays |  |
|-------------------------------|----------------------------------|--|
| Product or component type     | Plug-in relay                    |  |
| [In] rated current            | 3 A                              |  |
| Contacts type and composition | 4 C/O                            |  |
| Contacts material             | Gold flashed fine silver         |  |
| Contacts usage                | Hermetically sealed              |  |
| Series name                   | Miniature                        |  |
| [Uc] control circuit voltage  | 120 V                            |  |

## Complementary

| 782H   |   |
|--|---|
| 240 V AC                                       |   |
| 3 A at 120 V AC (on resistive load)            |   |
| ,  |   |
| 3 A at 30 V DC (on resistive load)             |   |
| 3900 Ohm                                       |   |
| Plug in  |   |
| 100 MA at 12 V AC                              |   |
| 100 MA at 12 V DC                              |   |
| 1.20 VA  |   |
| 100000 Cycles resistive load conforming to IEC |   |
| 10000000 Cycles                                |   |
| 20 ms  |   |
| 1600 V AC between coil and contact             |   |
| 1600 V AC between poles                        |   |
| 45 G   |   |
|  | 3 A at 120 V AC (on resistive load) 3 A at 240 V AC (on resistive load) 3 A at 30 V DC (on resistive load) 3900 Ohm  Plug in  100 MA at 12 V AC 100 MA at 12 V DC  1.20 VA  100000 Cycles resistive load conforming to IEC  10000000 Cycles 20 ms  1600 V AC between coil and contact 1600 V AC between poles |

## Environment

| Shock resistance                      | 10 gn                             |  |
|---------------------------------------|-----------------------------------|--|
| Environmental characteristic          | Hazardous location T5 40 °C tests |  |
| Vibration resistance                  | 6 gn (f = 1055 Hz)                |  |
| Ambient air temperature for operation | -4570 °C                          |  |
| Ambient air temperature for storage   | -6085 °C                          |  |
| Product certifications                | UL<br>CSA<br>CE                   |  |
| Height                                | 32.5 Mm                           |  |

Mar 9, 2022



| Width   | 22.75 Mm   |  |
|---|--|--|
| Depth   | 28.75 Mm   |  |
| Dealine Heite                                 |  |  |
| Packing Units                                 | PCE  |  |
| Unit Type of Package 1                        |  |  |
| Number of Units in Package 1                  | 1  |  |
| Package 1 Weight                              | 45 G   |  |
| Package 1 Height                              | 28.75 Mm   |  |
| Package 1 width                               | 22.75 Mm   |  |
| Package 1 Length                              | 28.75 Mm   |  |
| Unit Type of Package 2                        | CAR  |  |
| Number of Units in Package 2                  | 100  |  |
| Package 2 Weight                              | 5.4 Kg   |  |
| Package 2 Height                              | 18 Cm  |  |
| Package 2 width                               | 25.8 Cm  |  |
| Package 2 Length                              | 33.5 Cm  |  |
| Offer Sustainability Sustainable offer status | Green Premium product  |  |
| REACh Regulation                              | REACh Declaration  |  |
| REACh free of SVHC                            | Yes  |  |
| EU RoHS Directive                             | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration   |  |
| Toxic heavy metal free                        | Yes  |  |
| Mercury free                                  | Yes  |  |
| RoHS exemption information                    | €Yes   |  |
| China RoHS Regulation                         | € China RoHS Declaration   |  |
| Environmental Disclosure                      | Product Environmental Profile  |  |
| WEEE  | The product must be disposed on European Union markets following speci-<br>fic waste collection and never end up in rubbish bins   |  |
| California proposition 65                     | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |  |

Product Life Status: Commercialised

