5.96


6.62

5.63



## K10 Series 15A, DPCO





A plug-in general purpose DPCO miniature relay with 15A capacity. Compact in size it is ideal for installation in small equipment.

Double pole changeover Contact arrangement Contact material Contact rating Operate / release time Nominal coil power  $10^{7}$ Mechanical switching life

Approvals


Silver cadmium oxide 15A at 120V ac, 15A at 30V dc 13ms / 6ms (all relays) 0.9 W dc, 1.2 VA at 50 Hz ac approx.

1.5kV ac (coil-contact) Dielectric strength -45°C to + 70°C Temperature UL, CSA

			Unit Price		
Stock No.	Manf Ref'	Туре	1-24	25-99	100+
4951548	K10P11D15-6	DPCO-6VDC	5.04	4.54	4.28
4951542	K10P11D15-12	DPCO-12VDC	5.60	5.04	4.76
4951545	K10P11D15-24	DPCO-24VDC	5.63	5.07	4.79
4951536	K10P11A15-24	DPCO-24VAC	6.77	6.09	5.75
4951533	K10P11A15-120	DPCO-120VAC	6.91	6.22	5.87

## **DIN & PCB Mounted** Sockets for DPCO Relay





DIN and PCB mounted sockets for use with K10 style relays. IP20 finger protection with M3.5 captive terminal screws on the DIN sockets. PCB sockets are manufactured with "floating" loose terminals which permits them to align with holes in the circuit board and with the relay terminals. Hold down springs for relay retention are also available, please order separately.

Current rating 10A

Dielectric strength 2000V ac, 1 minute Approvals


UL, CSA

4951539 K10P11A15-240 DPCO-240VAC

			Unit Price		
Stock No.	Manf Ref'	Туре	1-24	25-99	100+
5501079	SH2B05C	DIN-SOCKET	3.12	2.96	2.81
5501085	SFA101	SPRING	0.30	0.29	0.27
4951356	27E489	PCB SOCKET	1.97	1.77	1.67

## **KUP Series** 10A, DPCO





A plug-in general purpose DPCO enclosed relay with 10A capacity.

Contact arrangement Contact material Contact rating Operate / release time Nominal coil power Mechanical switching life Dielectric strength Temperature

Terminals

Approvals

Double pole changeover Silver cadmium oxide 10A at 240V ac, 10A at 28V dc 15ms / 10ms (all relays) 1.2 W dc, 2 VA at 50 Hz ac approx.

2.2kV ac (coil-contact)

-45°C to + 55°C (ac), -45°C to + 70°C (dc)


4.75mm push-on

UL, CSA

			Unit Price		
Stock No.	Manf Ref'	Туре	1-24	25-99	100+
4951980	KUP11D15-12	DPCO-12VDC	5.99	5.39	5.09
4951983	KUP11D15-24	DPCO-24VDC	6.37	5.73	5.41
4951986	KUP11D15-48	DPCO-48VDC	6.37	5.73	5.41
4951956	KUP11A15-12	DPCO-12VAC	7.81	7.03	6.64
4951959	KUP11A15-120	DPCO-120VAC	6.73	6.06	5.72
4951962	KUP11A15-240	DPCO-240VAC	7.50	6.75	6.38

## **KUP Series** 10A, 3PCO





A plug-in general purpose 3PCO enclosed relay with 10A capacity. An optional test button version is available with a 24Vdc coil.

Contact arrangement Contact material Contact rating Operate / release time Nominal coil power Mechanical switching life Dielectric strength Temperature

Three pole changeover Silver cadmium oxide 10A at 120V ac, 10A at 28V dc 15ms / 10ms (all relays) 1.2 W dc, 2.7 VA at 50 Hz ac approx.

2.2kV ac (coil-contact)

 $-45^{\circ}$ C to + 45°C (ac), -45°C to + 70°C (dc)

Terminals 4.75mm push-on

Approvals UL, CSA

Stock No.	Manf Ref'	Туре	1-24	25-99	100+	
4952052	KUP14D15-6	3PCO-6VDC	8.52	7.67	7.24	
4952043	KUP14D15-12	3PCO-12VDC	6.86	6.17	5.83	
4952046	KUP14D15-24	3PCO-24VDC	6.91	6.22	5.87	
4952058	KUP14D25-24	TEST BUTTON	8.53	7.68	7.25	
4952040	KUP14D15-110	3PCO-110VDC	9.45	8.51	8.03	
4952004	KUP14A15-120	3PCO-120VAC	7.35	6.62	6.25	
4952010	KUP14A15-240	3PCO-240VAC	7.71	6.94	6.55	