


120 x 25mm Slimline Fans AC




A = 120, B = 120, C = 25, D = 4.2, F = 104.8

Powerful compact axial fans in a industry standard casing. Connection via 2 x 2.8mm push-ons which will also accept a pre-wired power lead.

Voltage (50/60Hz)	110VAC	230VAC
Air Flow (m <sup>3</sup> / h)	118	100
Power input (watts)	14	16
Rated speed (RPM)	2500	2200
Noise (dBA)	42	38
Bearings	Sleeve or Ball	
Casing	Aluminium alloy die casting, painted black	
Impeller	Black fibreglass reinforced plastic, UL94V-0	
Temperature	-40°C to +70°C	
Life expectancy	40,000 hours (ball), 30,000 hours (sleeve)	
Power lead	6 amp max., 915mm length	
Approvals	UL, CUL	

Stock No.	Manf Ref <sup>1</sup>	Type	Bearings	Unit Price		
				1-9	10-24	25+
7801049	A12A12HTB	110VAC	BALL	14.30	13.30	12.16
7801052	A12A23HTB	230VAC	BALL	14.30	13.30	12.16
7801055	A12A23HTS	230VAC	SLEEVE	11.50	10.70	9.78
7801001	C36	AC POWER LEAD		1.50	1.40	1.28

120mm x 38mm Fans AC & DC




A = 120, B = 120, C = 38, D = 4.3, F = 105

Powerful compact axial fans in an industry standard casing. AC fans are connected either via 2 x 2.8mm push-ons which will also accept a pre-wired power lead (915mm) or via 250mm wire leads, DC fans connected via wire leads (250mm length).

Voltage (50/60Hz)	12VDC	24VDC	110VAC	230VAC
Air Flow (m <sup>3</sup> / h)	178	178	167	150
Power input (watts)	6	7.68	20	23
Rated speed (RPM)	2800	2800	2950	2650
Noise (dBA)	42.8	42.8	48	43
Bearings	Ball (DC models), Ball or sleeve (AC models)			
Casing	DC (PBT, black), AC (aluminium alloy, black)			
Impeller	Black fibreglass reinforced plastic, UL94V-0			
Temperature	DC (-20°C to +70°C), AC (-40°C to +70°C)			
Life expectancy (hours)	DC 70,000, AC 40,000 (ball), 30,000 (sleeve)			
Power lead AC	6 amp max. 915mm length			
Approvals	UL, CUL, VDE			

Stock No.	Manf Ref <sup>1</sup>	Type	Bearings	Connection	Unit Price		
					1-9	10-24	25+
7801058	D12B04HWP	12VDC	BALL	250MM WIRE LEAD	15.00	13.95	12.75
7801061	D12B05HWP	24VDC	BALL	250MM WIRE LEAD	15.00	13.95	12.75
7801067	A12B12HWP	110VAC	BALL	250MM WIRE LEAD	13.10	12.18	11.14
7801064	A12B12HTB	110VAC	BALL	2 X 2.8MM PUSH-ONS	13.10	12.18	11.14
7801076	A12B12HTS	110VAC	SLEEVE	2 X 2.8MM PUSH-ONS	11.30	10.51	9.61
7801070	A12B23HWP	230VAC	BALL	250MM WIRE LEAD	13.10	12.18	11.14
7801073	A12B23HTB	230VAC	BALL	2 X 2.8MM PUSH-ONS	13.10	12.18	11.14
7801079	A12B23HTS	230VAC	SLEEVE	2 X 2.8MM PUSH-ONS	11.30	10.51	9.61
7801001	C36	AC POWER LEAD			1.50	1.40	1.28

127mm x 38mm Fans, AC



A = 127, B = 127, C = 38, D = 4.6, F = 113.3

High performance fan constructed from flame retardant polycarbonate. Connection via 2 x 2.8mm push-ons which will also accept a pre-wired power lead.

Voltage (50/60Hz)	230VAC, also available in 110VAC 60Hz		
Air Flow (m <sup>3</sup> / h)	188		
Power input (watts)	23		
Rated speed (RPM)	2700		
Noise (dBA)	43		
Bearings	Ball		
Casing	Aluminium alloy die casting, painted black		
Impeller	Black fibreglass reinforced plastic, UL94V-0		
Temperature	-40°C to +70°C		
Life expectancy	40,000 hours		
Power lead	6 amp max., 915mm length		
Approvals	UL		

Stock No.	Manf Ref <sup>1</sup>	Type	Bearings	Unit Price		
				1-9	10-24	25+
7801082	A13B23HTB	230VAC	BALL	19.05	17.72	16.19
7801001	C36	POWER LEAD		1.50	1.40	1.28