


M8, 1.5m Sensing, DC Standard Range




A flush mounted inductive proximity sensor designed to sense ferrous and non-ferrous metals. 3 wire DC operation, featuring short circuit and reverse polarity protection. Also available with extended range, non flush, short body, NPN and N/C please enquire.

Housing size	M8 (flush)
Nominal sensing range	1.5mm (steel), reduced for other metals
Supply voltage	10-30 volt DC
Rated output current	200 mA (transistor)
Temperature	-20 to +65°C
Built in LED	Yes
IP Rating	IP67
Body material	Brass Nickel plated
Connection type	M8 connector, 3 wire type

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10-24
3801533	IME08-1B5PS-ZTOS	PNP N/O	14.50	13.78	13.05

M12, 2mm Sensing, DC Standard Range




A flush mounted inductive proximity sensor designed to sense ferrous and non-ferrous metals. 3 wire DC operation, featuring short circuit and reverse polarity protection. Also available with extended range, non flush, short body, NPN and N/C please enquire.

Housing size	M12 (flush)
Nominal sensing range	2mm (steel), reduced for other metals
Supply voltage	10-30 volt DC
Rated output current	200 mA (transistor)
Temperature	-20 to +65°C
Built in LED	Yes
IP Rating	IP67
Body material	Brass Nickel plated
Connection type	M12 connector, 4 wire type

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10-24
3801536	IME12-02BPS-ZCOS	PNP N/O	14.26	13.55	12.83

M18, Sensing, DC Standard Range




A flush mounted inductive proximity sensor designed to sense ferrous and non-ferrous metals. 3 wire DC operation, featuring short circuit and reverse polarity protection. Also available with extended range, non flush, short body, NPN and N/C please enquire.

Housing size	M18 (flush)
Nominal sensing range	5mm (steel), reduced for other metals
Supply voltage	10-30 volt DC
Rated output current	200 mA (transistor)
Temperature	-20 to +65°C
Built in LED	Yes
IP Rating	IP67
Body material	Brass Nickel plated
Connection type	M12 connector, 4 wire type

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10-24
3801539	IME18-05BPS-ZCOS	PNP N/O	17.81	16.92	16.03

M30, Sensing, DC Standard Range



A flush mounted inductive proximity sensor designed to sense ferrous and non-ferrous metals. 3 wire DC operation, featuring short circuit and reverse polarity protection. Also available with extended range, non flush, short body, NPN and N/C please enquire.

Housing size	M30 (flush)
Nominal sensing range	10mm (steel), reduced for other metals
Supply voltage	10-30 volt DC
Rated output current	200 mA (transistor)
Temperature	-20 to +65°C
Built in LED	Yes
IP Rating	IP67
Body material	Brass Nickel plated
Connection type	M12 connector, 4 wire type

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10-24
3801542	IME30-10BPS-ZCOS	PNP N/O	21.46	20.39	19.31