


**ATEX Limit Switch  
EEx 12 Metal**




An explosion proof metal bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Snap action contacts.

- Actuator Plain plunger
- Housing Metal, GD-AL alloy
- Contact arrangement Snap action changeover
- Electrical rating 5A
- IP Rating IP65
- Temperature -20°C to +60°C
- Termination Cable 1M
- Ex Certification EX II 2G EEx d II C T6
- Ex Certification EX II 2D IP65 T80
- Approvals PTB 03 ATEX 1067X

Stock No.	Manf Ref <sup>1</sup>	Type	Unit Price		
			1-4	5-9	10+
2441001	EEX12	PLAIN PLUNGER	55.03	53.38	51.73

**ATEX Limit Switch  
EEx 12 Metal**




An explosion proof metal bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Snap action contacts.

- Actuator Ball plunger
- Housing Metal, GD-AL alloy
- Contact arrangement Snap action changeover
- Electrical rating 5A
- IP Rating IP65
- Temperature -20°C to +60°C
- Termination Cable 1M
- Ex Certification EX II 2G EEx d II C T6
- Ex Certification EX II 2D IP65 T80
- Approvals PTB 03 ATEX 1067X

Stock No.	Manf Ref <sup>1</sup>	Type	Unit Price		
			1-4	5-9	10+
2441003	EEX12KU	BALL PLUNGER	56.93	55.22	53.51

**ATEX Limit Switch  
EEx 12 Metal**




An explosion proof metal bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Snap action contacts.

- Actuator Roller plunger
- Housing Metal, GD-AL alloy
- Contact arrangement Snap action changeover
- Electrical rating 5A
- IP Rating IP65
- Temperature -20°C to +60°C
- Termination Cable 1M
- Ex Certification EX II 2G EEx d II C T6
- Ex Certification EX II 2D IP65 T80
- Approvals PTB 03 ATEX 1067X

Stock No.	Manf Ref <sup>1</sup>	Type	Unit Price		
			1-4	5-9	10+
2441005	EEX12R	ROLLER PLUNGER	54.87	53.22	51.58

**ATEX Limit Switch  
EEx 12 Metal**



An explosion proof metal bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Snap action contacts.

- Actuator Roller lever
- Housing Metal, GD-AL alloy
- Contact arrangement Snap action changeover
- Electrical rating 5A
- IP Rating IP65
- Temperature -20°C to +60°C
- Termination Cable 1M
- Ex Certification EX II 2G EEx d II C T6
- Ex Certification EX II 2D IP65 T80
- Approvals PTB 03 ATEX 1067X

Stock No.	Manf Ref <sup>1</sup>	Type	Unit Price		
			1-4	5-9	10+
2441007	EEX12D	ROLLER LEVER	66.45	64.46	62.46