


**ATEX Limit Switch
EEx 14 Plastic**




An explosion proof plastic bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with snap action changeover or 2 N/C positive break contacts.

Actuator Plain plunger
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +65°C
 Termination Cable 1M
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification EX II 2D IP65 T80
 Approvals PTB 03 ATEX 1070X/1006X/1069X

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10+
2441036	EEX1410/1S	PLAIN PLUNGER	48.03	46.59	45.15

**ATEX Limit Switch
EEx 14 Plastic**




An explosion proof plastic bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with snap action changeover or 2 N/C positive break contacts.

Actuator Ball Plunger
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +65°C
 Termination Cable 1M
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification EX II 2D IP65 T80
 Approvals PTB 03 ATEX 1070X/1006X/1069X

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10+
2441038	EEX14KU10/1S	BALL PLUNGER	49.12	47.65	46.17

**ATEX Limit Switch
EEx 14 Plastic**




An explosion proof plastic bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with snap action changeover or 2 N/C positive break contacts.

Actuator Roller plunger
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +65°C
 Termination Cable 1M
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification EX II 2D IP65 T80
 Approvals PTB 03 ATEX 1070X/1006X/1069X

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10+
2441040	EEX14R10/1S	ROLLER PLUNGER	49.84	48.34	46.85

**ATEX Limit Switch
EEx 14 Plastic**



An explosion proof plastic bodied limit switch, certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with snap action changeover or 2 N/C positive break contacts.

Actuator Roller lever
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +65°C
 Termination Cable 1M
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification EX II 2D IP65 T80
 Approvals PTB 03 ATEX 1070X/1006X/1069X

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10+
2441042	EEX14D10/1S	ROLLER LEVER	51.32	49.78	48.24