


**ATEX Limit Switch IP67
EEx 95 Plastic**




An explosion proof plastic bodied limit switch housed in a DIN50047 standard case allowing direct drop to replace non ex standard limit switches. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator Plain plunger
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP67
 Temperature -20°C to +65°C
 Termination Cable gland, wiring compartment
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification Ex II 2D IP65 T80
 Approvals DMT01 ATEX E118

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441050	EEX95W10/1S	PLAIN PLUNGER	112.96	109.57	106.18

**ATEX Limit Switch IP67
EEx 95 Plastic**




An explosion proof plastic bodied limit switch housed in a DIN50047 standard case allowing direct drop to replace non ex standard limit switches. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator Roller plunger
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP67
 Temperature -20°C to +65°C
 Termination Cable gland, wiring compartment
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification Ex II 2D IP65 T80
 Approvals DMT01 ATEX E118

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441052	EEX95R10/1S	ROLLER PLUNGER	114.13	110.71	107.28

**ATEX Limit Switch IP67
EEx 95 Plastic**



An explosion proof plastic bodied limit switch housed in a DIN50047 standard case allowing direct drop to replace non ex standard limit switches. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator Rocking roller
 Housing Plastic, glass fibre reinforced
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP67
 Temperature -20°C to +65°C
 Termination Cable gland, wiring compartment
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification Ex II 2D IP65 T80
 Approvals DMT01 ATEX E118

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441054	EEX95D10/1S	ROCKING ROLLER	120.74	117.12	113.50