

**ATEX Limit Switch IP66
EEx 95 Salt Spray**



An explosion proof plastic bodied limit switch with stainless steel components designed to offer protection from salt spray. These switches are tested to IP66 which means that 100 litres per minute of high pressure salt water are sprayed at varying directions corresponding to offshore conditions. Limit switch housed in a DIN50047 standard case allowing direct drop to replace non ex standard limit switches. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator	Plain plunger
Housing	Plastic, glass fibre reinforced
Contact arrangement	1 N/O and 1 N/C positive break
Electrical rating	6A at 250Vac
IP Rating	IP66 salt spray
Temperature	-20°C to +65°C
Termination	Cable gland, wiring compartment
Ex Certification	EX II 2G EEx d II C T8
Ex Certification	Ex II 2D IP65 T80
Approvals	DMT01 ATEX E118

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10+
2441051	EEX95W10/1S-IP66	PLAIN PLUNGER	161.45	156.61	151.76

**ATEX Limit Switch IP66
EEx 95 Salt Spray**



An explosion proof plastic bodied limit switch with stainless steel components designed to offer protection from salt spray. These switches are tested to IP66 which means that 100 litres per minute of high pressure salt water are sprayed at varying directions corresponding to offshore conditions. Limit switch housed in a DIN50047 standard case allowing direct drop to replace non ex standard limit switches. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator	Rocking roller
Housing	Plastic, glass fibre reinforced
Contact arrangement	1 N/O and 1 N/C positive break
Electrical rating	6A at 250Vac
IP Rating	IP66 salt spray
Temperature	-20°C to +65°C
Termination	Cable gland, wiring compartment
Ex Certification	EX II 2G EEx d II C T8
Ex Certification	Ex II 2D IP65 T80
Approvals	DMT01 ATEX E118

Stock No.	Manf Ref ¹	Type	Unit Price		
			1-4	5-9	10+
2441055	EEX95D10/1S-IP66	ROCKING ROLLER	162.81	157.93	153.04