


**ATEX Limit Switch
EEx 355 Metal**




An explosion proof metal bodied limit switch. Although wider than the DIN50041 sizes the fixing hole centres are the same at 30mm separation. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator Plain plunger
 Housing Metal Zinc diecast, enamelled
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +60°C
 Termination Cable gland, wiring compartment
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification Ex II 2D IP65 T80
 Approvals DMT01 ATEX E178

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441072	EEX355S10/1S	PLAIN PLUNGER	127.72	123.38	119.57

**ATEX Limit Switch
EEx 355 Metal**




An explosion proof metal bodied limit switch. Although wider than the DIN50041 sizes the fixing hole centres are the same at 30mm separation. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator Roller plunger
 Housing Metal Zinc diecast, enamelled
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +60°C
 Termination Cable gland, wiring compartment
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification Ex II 2D IP65 T80
 Approvals DMT01 ATEX E178

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441074	EEX355R10/1S	ROLLER PLUNGER	128.34	124.49	120.64

**ATEX Limit Switch
EEx 355 Metal**




An explosion proof metal bodied limit switch. Although wider than the DIN50041 sizes the fixing hole centres are the same at 30mm separation. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator Roller lever
 Housing Metal Zinc diecast, enamelled
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +60°C
 Termination Cable gland, wiring compartment
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification Ex II 2D IP65 T80
 Approvals DMT01 ATEX E178

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441076	EEX3554VH10/1S	ROLLER LEVER	133.35	129.35	125.35

**ATEX Limit Switch
EEx 355 Metal**



An explosion proof metal bodied limit switch. Although wider than the DIN50041 sizes the fixing hole centres are the same at 30mm separation. Dual certified for Ex zones 1 and 2 as well as dust zones 21 and 22. Slow action positive break contacts. Available also with 2 N/C positive break contacts and 1 N/O / 1 N/C overlapping positive break.

Actuator Long roller
 Housing Metal Zinc diecast, enamelled
 Contact arrangement 1 N/O and 1 N/C positive break
 Electrical rating 6A at 250Vac
 IP Rating IP65
 Temperature -20°C to +60°C
 Termination Cable gland, wiring compartment
 Ex Certification EX II 2G EEx d II C T6
 Ex Certification Ex II 2D IP65 T80
 Approvals DMT01 ATEX E178

Stock No.	Manf Ref'	Type	Unit Price		
			1-4	5-9	10+
2441078	EEX3554V3H10/1S	LNG ROLLER LVR	137.44	133.32	129.19