



**T92 Series
30A, DP N/O, Sealed**



Terminal Arrangements (bottom view)



Board Layout


A high capacity PCB power relay with DPNO contacts capable of switching 30A. Fully sealed for immersion cleaning.

- Contact arrangement Double pole normally open
- Contact material Silver cadmium oxide
- Contact rating 30A at 240V ac, 20A at 28V dc
- Contact load min. 0.5A at 12V dc, 0.5A at 12V ac
- Operate / release time 15ms / 10ms
- Coil resistance.ohm 86
- Nominal coil power 1.7 W
- Dielectric strength 4kV ac (coil-contacts)
- Mechanical switching life 5×10^6
- Temperature -40°C to + 85°C
- Approvals UL, CSA, VDE
- Overall dimensions L = 52.3, W = 34.5, H = 30.7


Note:Remove tape over vent hole after soldering and cleaning

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4952361	T92S7D12-12	DPNO-12VDC	7.25	6.53	6.16
4952364	T92S7D12-24	DPNO-24VDC	7.25	6.53	6.16

**T92 Series
30A, DPCO, Sealed**



Terminal Arrangements (bottom view)



Board Layout

A high capacity PCB power relay with DPCO contacts capable of switching 30A. Fully sealed for immersion cleaning.

- Contact arrangement Double pole changeover
- Contact material Silver cadmium oxide
- Contact rating 30A at 240V ac
- Contact load min. 0.5A at 12V dc, 0.5A at 12V ac
- Operate / release time 15ms / 10ms
- Coil resistance.ohm 86 (12V), 350 (24V)
- Nominal coil power 1.7 W
- Dielectric strength 4kV ac (coil-contacts)
- Mechanical switching life 5×10^6
- Temperature -40°C to + 85°C
- Approvals UL, CSA, VDE
- Overall dimensions L = 52.3, W = 34.5, H = 30.7

Note:Remove tape over vent hole after soldering and cleaning

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4952352	T92S11D12-24	DPCO-24VDC	7.25	6.53	6.16

