

**XT Series Plug-in
16A, SPCO**



The XT series relays are a new generation of plug in relays featuring a clear case and extra strong pins for greater mechanical strength. Also features a manual test lever as standard and a sensitive 400mW coil with built in led indication and suppression diode. Suitable for RT series DIN rail sockets.

Contact arrangement	Single pole changeover
Contact material	Silver nickel
Contact rating	16A at 230V ac, 30V dc
Nominal coil power	400mW
Mechanical switching life	10 million dc, 5 million ac version
Dielectric strength	4kV/8mm coil contact gap vde 0700 class 2
Temperature	-40°C to + 85°C
Approvals	UL, VDE, CSA

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4954913	XT374LC4	SPCO-12VDC	3.23	2.91	2.75
4954907	XT374T30	SPCO-230VAC	5.29	4.76	4.50

**XT Series Plug-in
8A, DPCO**



The XT series relays are a new generation of plug in relays featuring a clear case and extra strong pins for greater mechanical strength. Also features a manual test lever as standard and a sensitive 400mW coil with built in led indication and suppression diode. Suitable for RT series DIN rail sockets.

Contact arrangement	Double pole changeover
Contact material	Silver nickel
Contact rating	8A at 230V ac, 30V dc
Nominal coil power	400mW
Mechanical switching life	10 million dc, 5 million ac version
Dielectric strength	4kV/8mm coil contact gap vde 0700 class 2
Temperature	-40°C to + 85°C
Approvals	UL, VDE, CSA

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4954916	XT484LC4	DPCO-12VDC	3.84	3.46	3.26
4954910	XT484T30	DPCO-230VAC	5.80	5.22	4.93

**RT DIN Rail Socket
5mm Pinning**



A din rail socket suitable to mount relays with 5mm pinning from the XT range of relays. Can be used with double pole or single pole relay. Note socket is rated to 12A per terminal. If using full 16A of single pole relay rating ensure terminals 11-21, 12-22 and 14-24 are bridged to enhance the rating. Available with a retaining clip to hold relay in place and a variety of protection and indication modules.

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
4954295	RT78726	5MM PINNING	2.20	1.98	1.87
4954296	RT17016	CLIP	0.12	0.11	0.10
4953039	PTMT00A0	DIODE MODULE	1.50	1.35	1.28
4954033	PTML0524	LED MODULE	1.58	1.03	0.71
4954036	PTML0024	6 to 24 VAC/DC LED/DIODE	1.58	1.03	0.71
4954039	PTML0730	MODULE 6 to 24 VDC LED MODULE FOR 110 to 230 VAC	1.62	1.05	0.73