

**Buzzer
107 Series**



A low current electronic buzzer for 22.5mm panel mounting. 2400hz continuous tone (12 Vdc 3200Hz). 80db sound output at 10cm.

Housing	PC
Current consumption	24Vdc 8mA
IP Rating	IP65
Temperature	minus 20 to +50 Deg C
Termination	Connector plug with screw terminals
Dimensions	Diam 28.2mm, Depth behind panel 48.5mm ex plug

			Unit Price
Stock No.	Manf Ref'	Type	1-4
2201080	107-000-54	12VDC	29.74
2201082	107-000-75	24VDC	18.70
2201001	107-000-68	230VAC	19.63

**Buzzer
109 Series**



An electronic buzzer for 22.5mm panel mounting. 2100Hz continuous tone. High output of 80db at 1m.

Housing	PC
Current consumption	24Vdc 25mA
IP Rating	IP65
Temperature	minus 20 to +50 Deg C
Termination	Connector plug with screw terminals
Dimensions	Diam 65.0mm, Depth behind panel 23.5mm ex plug

			Unit Price
Stock No.	Manf Ref'	Type	1-4
2201084	109-000-75	24VDC	33.53
2201086	109-000-68	230VAC	36.67

**LED Buzzer combination
150 Series**



A permanent led combined with an electronic buzzer suitable for 22.5mm panel mounting. 2800Hz continuous tone. High output of 80db at 1m.

Housing	PC
Current consumption	24Vdc 50mA
IP Rating	IP65
Temperature	minus 20 to +50 Deg C
Termination	Connector plug with screw terminals
Dimensions	Diam 49.5mm, Depth behind panel 52mm ex plug

			Unit Price
Stock No.	Manf Ref'	Type	1-4
2201088	150-100-55	24VDC RED	40.31
2201090	150-300-55	24VDC YELLOW	40.31
2201092	150-100-68	230VAC RED	42.96
2201094	150-300-68	230VAC YELLOW	42.96