



UF3 Series Relay 10A, 3PCO



Viewed on connector pins

Connection diagram viewed from pins



Universal 3PCO plug in relay with silver nickel contacts for 11 pin bases. Featuring a manual push to test button, mechanical flag indicator and manual override lever, which can be used as a locking lever whilst commissioning.

- Contact arrangement: Three pole changeover
- Contact material: Silver nickel
- Contact rating: 10A at 250V ac
- Contact load min.: 20mA at 10V dc
- Min. switching current: 50mA at 20V dc
- Operate / release time: 14ms / 10ms
- Nominal coil power: 1.2 W dc, 2.2 VA at 50 Hz ac approx.
- Mechanical switching life: 20 x 10⁵
- Insulation voltage: 2.5kV ac (coil-contact)
- Temperature: -25°C to + 60°C (DC), -25°C to + 40°C (AC)

Relays with integral LED indication are also available, please consult sales.

The DIN socket is 10A rated. It has IP20 finger protection screw terminals with clear terminal marking. Sockets include wire retaining clip.


Din Base for 11 Pin Relay



- Current rating: 10A
- Positive terminal: Term A1 (for relays with diode)

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
1101093	UF3.12VDC1	12VDC	5.27	4.74	4.48
1101102	UF3.24VDC1	24VDC	5.27	4.74	4.48
1101099	UF3.24VAC1	24VAC	5.27	4.74	4.48
1101090	UF3.115VAC1	115VAC	5.85	5.27	4.97
1101096	UF3.230VAC1	230VAC	5.85	5.27	4.97
Modules					
1101150	Z393	DIN BASE	2.73	2.46	2.32

Din Base for 11 Pin Relay Indication & Protection Modules





Modules for 11 pin DIN base

Din mounting base for 11 pin relays with the additional facility of adding plug-in protection and indication modules. It has IP20 finger protection screw terminals with clear terminal marking. Sockets include wire retaining clip.

- Current rating: 10A
- Positive terminal: Term A1 (for relays with diode)

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
1101153	Z396	DIN BASE	3.96	3.56	3.37
1101156	Z396.50	DIODE	0.71	0.64	0.60
1101159	Z396.52	LED/DIODE 24VDC	1.17	1.05	0.99
1101162	Z396.58	LED/VARISTOR 230VAC	2.30	2.07	1.96

Terminal Block Relay 6A, SPCO



Slimline relay for DIN rail mounting with SPCO contacts rated to 6A at 400V ac. 6mm width. Relay status indication by LED. Integrated diodes for coil suppression and polarity protection.

- Contact arrangement: Single pole changeover
- Contact rating: 6A at 400V ac
- Contact load min.: 100mA
- Nominal coil power: 0.3W dc
- Electrical switching life: 10⁵
- Approvals: UL, CSA, VDE

Stock No.	Manf Ref'	Type	Unit Price		
			1-24	25-99	100+
3502724	007 100.04	24VDC	8.90	8.63	8.37