




UD-250A Single Pole Distribution Block



- Connects ERICO® FLEXIBAR® on line side using FLG-250 Flat Terminal Connection
- Tinned copper block allows for copper or aluminum conductor connections
- Screw retaining cover is hinged and removable
- Design allows for visual inspection of conductor and confirmation of connection
- Gangable for building multi-pole power blocks
- Easily clips onto DIN rail or mounts to panel with screws
- 95% fill ratio
- Halogen free
- RoHS compliant



Material: Copper, Thermoplastic
Finish: Tinned

Part Number	UD-250A
Article Number	569040
Max Current Rating, IEC	250 A
Max Current Rating, UL/CSA	255 A
Short Term Withstand Current (Icw) 1s	24.5 kA
Peak Short Circuit Current (Ipk)	51 kA
Short Circuit Current Rating (SCCR)	100 kA
Max Working Voltage, IEC (Ui)	1,000 VAC/DC
Max Working Voltage, UL (Vin)	600 V
Line Side Number of Connections	1
Line Side Compact Stranded Wire Size	35 – 120 mm ²
Line Side Wire Size	#6 – 250 kcmil
Load Side Number of Connections	11
Load Side Compact Stranded Wire Size	(2) 6 – 35 mm ² (4) 2,5 – 10 mm ² (5) 2,5 – 16 mm ²
Load Side Stranded Wire Size - Ferrule	(2) 6 - 25 mm ² (4) 2,5 - 10 mm ² (5) 2,5 - 16 mm ²
Load Side Wire Size	(2) #8 - #1



Part Number	UD-250A
	(4) #8 - #6 (5) #8 - #4
Enclosure Rating	IP 20
Depth (D)	50 mm
Height (H)	96 mm
Width (W)	49 mm
Unit Weight	0.42 kg
Certification Details	UL® 1059
Flammability Rating	UL® 94V-0
Complies With	IEC® 60947-7-1

Design Guideline for Distribution Blocks, Power Blocks and Power Terminals										
Derating according to Ambient* Temperature (°C) to maintain working temperature of 85°C										
Ambient Temperature (°C)	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°
Derating Coefficient (d)	1	1	1	0.94	0.88	0.82	0.75	0.67	0.58	0.47
*environment around the terminal blocks inside the enclosure										

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

